

# TITAN



72 cell Poly-Crystalline Silicon Photovoltaic Module

## Key Features



10  
2

## STC Electrical Characteristics

|               | 330   | 325   | 320   | 315   | 310   | 305   |
|---------------|-------|-------|-------|-------|-------|-------|
|               | 330   | 325   | 320   | 315   | 310   | 305   |
|               | 3     | 3     | 3     | 3     | 3     | 3     |
|               | 45.20 | 44.90 | 44.60 | 44.30 | 44.00 | 43.7  |
|               | 18    | 9.10  | 9.03  | 93    | 86    | 8,78  |
| power         | 7 0   | 7.70  | 7.50  | 7.30  | 37.10 | 36.80 |
| power current | 71    | 62    | 53    | 44    | 36    | 29    |
|               | 08    | 6 84  | 58    | 32    | 16 06 | .80   |


Temperature Characteristics

|  |   |    |
|--|---|----|
|  | ° | 6  |
|  | ° | 34 |
|  | ° | 44 |

Mechanical Characteristics

|  |              |      |
|--|--------------|------|
|  | 156x156 poly |      |
|  | white        |      |
|  | 950          | 0 50 |
|  | 23           |      |
|  | 3 diode MC4  |      |
|  | 27           |      |
|  | 7            | 48   |

IV Curve



Quality Assurance

